

Technical Specifications

Parameters	Value
Motor RPM	1400
Cooling Area*	15 sq.mt / 150 sq.ft
Air throw Distance*	10 mt. / 33 ft.
Air delivery	1100 m ³ .hr/650 cfm
Electrical*	
230V / 50-60 Hz	
Wattage	80 W
Max. Current	0.40 amp
110V / 60Hz	
Wattage	90 W
Max. Current	0.80 amp
Blower / Fan	Blower
Blower Diameter	132 mm / 5 inch
Speed Control	Three
Water tank capacity	16 ltr / 4.25 gallons (US)
Portability	Castors
Vertical louvre movement	Automatic
Operates on inverter	Yes
Humidity Control	Yes
Dust filter net	Yes
Water Level Indicator	Yes
Cooling Media	Aspen
Dimensions (Product)	
Length	450 mm / 18 inch
Breadth	287 mm / 11 inch
Height	653 mm / 26 inch
Dimensions (Carton)	
Length	493 mm / 19 inch
Breadth	329 mm / 13 inch
Height	700 mm / 28 inch
Weight	
Product	10 kg / 22 lbs
Incl. Packaging	12kg / 26 lbs
Certifications	CE, SASO
No.of units per 40 ft High Cube Container	614

*Under test conditions, actual may vary depending on the ambient conditions and the heat load. All specifications are approximate and may vary within ± 10% of the specified value. All products are subject to continuous improvement. The company reserves the right to change specifications without any prior notice. Inverter has to be of appropriate rating and of good quality.



Seal of Conformity with European directives




Saudi Arabian Standards Organisation



www.symphonycomfort.com
e-mail: international@symphonycomfort.com

Surround

Cools upto 15 sq.mt. / 150 sq.ft.*



03 08

Air coolers with Lowest Power Consumption



With three side cooling pads this air cooler is ideal for...



Surround

Cools upto 15 sq.mt. / 150 sq.ft.*

With cooling pads on three sides for the first time ever in its category, Surround is truly the most compact and powerful. So, surrender...



Low power consumption of only 80 watts / 0.08 units per hour*

• Three side wood wool cooling pads for great cooling



• Humidity control



• Large tank capacity



• 10 mt. (33 ft.)* air throw



• 3 Speed motor



* Wattage at 230/50-60 Hz